



PORTABLE DENSITY METER

DM-250.2

IN PROCESS TO EXCELLENCE

Specifications

Measuring range:

Density	0... 3 g/cm ³ (0... 3000 kg/m ³)
Density Standard calibration	0.6... 1.2 g/cm ³ (600... 1200 kg/m ³)
	0.9... 1.8 g/cm ³ (900... 1800 kg/m ³)
Temperature	-40... +85°C (-40... +185°F)

Accuracy:

Density	±0.0003 or ±0.0005 g/cm ³ (±0.3 or ±0.5 kg/m ³)
Temperature	±0.1°C (±0.2°F) or ±0.2°C (±0.4°F)

Repeatability:

Density	±0.00015 or ±0.00025 g/cm ³ (±0.15 or ±0.25 kg/m ³)
Temperature	±0.1°C (±0.2°F)

Resolution:

Density	0.0001 g/cm ³ (0.1 kg/m ³)
Temperature	0.01°C (0.02°F)

Supported measuring units

Real Density: g/cm³, kg/m³, lb/gal, lb/ft³; API; SG
 Referred Density: at 15°C, 20°C, 60°F; API60; SG60
 Tables ASTM D 1250
 Alcohol Tables
 Temperature in °C or °F

Ambient temperature

-40... +85°C (-40... +185°F)

Depth of submersion

Up to 30 meters (100 ft.)

Sensor:

Type	Vibrating element (Resonance principle)
Material	Stainless steel SS 316 L; NiSpan C; Hastelloy C22

Intrinsically safe:

Controller	ATEX II (2G) EEx ib [ia] IIB T4
Level block with sensor	ATEX II 1G EEx ia IIB T4

Power supply

2 x NiMH 3.6V-1500 mAh

Operating time without charging

Appr. 12 hours

Dimensions, weight:

Controller	180 x 80 x 40 mm (7.1 x 3.2 x 1.6"), 0.6 kg (1.3 lb)
Level block with sensor	420 x 245 x 140 mm (16.5 x 9.7 x 5.5"), 4 kg (8.8 lb)

Temperature compensation

Automatic

Viscosity compensation

Automatic

Data handling

Backlighted LCD display (2x16)
 Local memory up to 2000 results
 Build in Bluetooth for data transfer to printer or PC
 Optional Windows - based software

Advantages

- Direct density measurement
- Density Profile
- Temperature Profile
- Automatic temperature compensation
- No sampling required
- ATEX, IEC Hazloc certification
- Safe operation, low maintenance
- At any depths up to 30 meters
- Economical and easy to operate
- Measures highly viscous liquids up to 2000 cP
- Rigid construction for heavy duty outdoor operation
- Local results storage and Bluetooth data transfer

Applications


- Petroleum industry
- Ethanol production
- Food & Beverages
- Chemical industry
- Cosmetic industries
- Pharmaceutical industry

Delivered in compact carrying case



CASE

Able to download the measurements to PC;
 Multifunctional software produces's
 measurement results in user-convenient form;
 Compatible for a Windows XP/Vista/7.



SOFTWARE

Immediate printout of the measurements;
 No need for PC.



BLUETOOTH PRINTER

For more information please visit www.lemis-process.com



USA

LEMIS USA, Inc.

2121 Golden Road, Suite 2A
 The Woodlands
 TX 77380, USA
 Ph.: +1 281 465 8441
 Fax: +1 281 465 8224

EUROPE

AS LEMIS Baltic

26 Ganibu dambis
 Riga, LV-1005
 Latvia, EU
 Ph.: +371 6738 3223
 Fax: +371 6738 3270

INDIA

LEMIS India PVT LTD

603, Platinum Technopark, Plot-17/18
 Sector-30A, Vashi
 Vashi - Navi Mumbai. 400705, INDIA
 Ph.: +91 22 6721 5655
 Fax: +91 22 6794 2666

E-mail: info@lemis-process.com