



solidpartners  
provensolutions

Automated Multi-Range Capillary Viscometer

**HVM 472**

**PAC**  
www.paclp.com

**U.S.A.**

PAC, LP | 8824 Fallbrook Drive | Houston, Texas 77064  
T: +1 800.444.TEST | O: +1 281.940.1803 | F: +1 281.580.0719  
sales.usa@pacpl.com | service.usa@pacpl.com

**FRANCE**

BP 70285 | Verson | 14653 CARPIQUET Cedex  
T: +33 231 264 300 | F: +33 321 266 293  
sales.france@pacpl.com | PACServiceFrance@pacpl.com

**GERMANY**

Badstrasse 3-5 | P.O.Box 1241 | D-97912 Lauda-Königshofen,  
T: +49 9343 6400 | F: +49 9343 640 101  
sales.germany@pacpl.com | service.germany@pacpl.com

**SINGAPORE**

61 Science Park Road | #03-09/10 The Galen  
Singapore Science Park III | Singapore 117525  
T: +65 6412 0890 | F: +65 6412 0899  
sales.singapore@pacpl.com | service.singapore@pacpl.com

**NETHERLANDS**

P.O.Box 10.054 | 3004 AB Rotterdam  
Innsbruckweg 35 | 3047 AG Rotterdam  
T: +31 10 462 4811 | F: +31 10 462 6330  
sales.netherlands@pacpl.com | service.netherlands@pacpl.com

**RUSSIA**

Shabolovka Street | 34, Bldg. 2 | 115419 Moscow  
T: +7 495 617 10 86 | F: +7 495 913 97 65  
sales.russia@pacpl.com | service.russia@pacpl.com

**CHINA**

Room 1003, Sunjoy Mansion | No. 6 RiTan Rd.  
Chao Yang District | Beijing 100020  
T: +86 10 650 72236 | F: +86 10 650 72454  
sales.china@pacpl.com | service.china@pacpl.com

**INDIA**

403, Sentinel, Central Avenue, Hiranandani Gardens  
Powai, Mumbai - 400 076 INDIA  
T: +91-22-2570 3636  
sales.india@pacpl.com | service.india@pacpl.com

**MIDDLE EAST**

A1 Quds Street, A1 Tawar road | LIU#H13 Dubai Airport Freezone  
Near Dubai Airport (terminal 2) | P.O.Box #54781 | Dubai, UAE  
T: +971 04 2947 995 | F: +971 04 2395 465  
sales.middleeast@pacpl.com | service.middleeast@pacpl.com

**SOUTH KOREA**

#621 World Vision Building | 24-2, Youido-dong  
Seoul 150-010  
T: +82 2785 3900 | F: +82 2785 3977  
sales.southkorea@pacpl.com | service.southkorea@pacpl.com

**THAILAND**

26th Floor, M. Thai Tower | All Seasons Place  
87 Wireless Road | Lumpini, Phatumwan | Bangkok 10330  
T: +66 2627 9410 | F: +662627 9401  
sales.thailand@pacpl.com | service.thailand@pacpl.com

PAC Authorized Representatives are also located in most countries worldwide. For more information visit [www.paclp.com](http://www.paclp.com)


**HERZOG BY PAC**

Herzog, originally established in 1937, is a long-established comprehensive line of laboratory instruments for testing distillation, flash point, vapor pressure, bitumen testing, cold flow properties, viscosity and other physical properties of materials.

**SPECIFICATIONS**

GENERAL INFORMATION	
Ordering Information	HVM472 Automated Multi-Range Capillary Viscometer. Stand-Alone configuration with two baths, integrated auto samplers and automatic dual solvents cleaning system for continuous operation.
Standard Test Methods	ASTM D445, IP 71 Section 1, ISO 3104, EN ISO 3104
OPERATION	
Performance Viscosity range	0.5 - 5000mm <sup>2</sup> /s (Dual 100-fold atlantic capillaries)
Bath temperature control	20–150°C (68 to 302°F), user programmable ≤100°C: better than ± 0.01°C (±0.02°F) >100°C: better than ±0.03°C (±0.05°F) Proportional heat control resolution 0.001°C, high velocity bath media circulation
Sample induction	Via integrated 26 position auto samplers (one sampler per bath), which automatically draw sample directly from 18ml / 4 ml vial. Programming window automatically opens when samples are placed, allowing user to key in sample ID and start testing.
Detection	Two multi-range tubes (see viscosity range above) Thermal NTC meniscus detection/timing
Documentation	Numeric display; output to printer by parallel Centronics interface; output to LIMS or HLIS vial serial standard port
Auto Cleaning	Dual solvent system with programmable cycle parameters; low solvent usage (no external vacuum pump required) Built-in automatic detection of cleaning solvent availability, Kalrez seals compatible with various solvents, including acetone; 4- solvent cleaning available as an option
Diagnostics & Calibrations	Real time status display and control for all mechanical and electrical systems locally or with optional network
Utility requirements	230/115/100 VAC, 50–60 Hz configurable/selectable
Dimensions & Weight	49 cm W x 75 cm D x 127 cm H; 90 kg (99 kg with bath liquid) 19.3 in W x 29.6 in D x 50 in H; 199 lbs (219 lbs with bath liquid)
ACCESSORIES	
PAC IRIS Software features for HVM 472	<ul style="list-style-type: none"> <li>• Run Control</li> <li>• Results</li> <li>• Calibration</li> <li>• Reports</li> <li>• Quality Control</li> <li>• Diagnostics</li> <li>• Method Definition</li> <li>• Test Start</li> <li>• Results Evaluation</li> <li>• Instrument Parameters</li> </ul>
Ticket Printer	For stand-alone use or with option PC; 40 columns endless paper
Cooling Accessories	External circulation cooler: obtains bath temperatures from 20° to 40°C Cooling control system: recommended if external cooler is used; prevents bath cooling when a temperature above 40°C is selected; one required for each measuring position
Slop Accessories	Sensor: detects a full slop container and prevents overflow Container: for waste solvent (according to safety regulations)
Sample Beakers	Standard or 4ml: - Plastic disposable beaker (100°C max) - Glass disposable beaker (150°C max)
Adapter and Filling Support	Adapter for low volume option; Filling support for single vial filling; Tray 20 positions for low volume vial with filling support Tray 20 positions for standard beaker with filling support for FR capillary
Multi-Range Capillary	Standard: 100 fold range; 12 gradings Fast Run: 20 fold range; 10 gradings: 0.5–10; 1–20 up to 30–600 mm <sup>2</sup> /s
PC and Printer	Contact your PAC representative for details

Continuing research and development may result in specifications or appearance changes at any time



**HERZOG**  
by PAC

**The Advanced Solution for Unattended, Continuous Viscosity Testing**

- Precise and accurate analysis results
- Easy and safe operation with advanced system automation
- Flexible and modular design for fast adaptation to both current & future analysis needs
- In compliance with ASTM D445, IP 71 Section 1, ISO 3104 and EN ISO 3104

Copyright 2014/1 PAC L.P. All rights reserved 820-671

[www.paclp.com](http://www.paclp.com)



USA • FRANCE • GERMANY • NETHERLANDS • UAE • RUSSIA • CHINA • SINGAPORE • SOUTH KOREA • THAILAND • INDIA




## AUTOMATED MULTI-RANGE CAPILLARY VISCOMETER

The Herzog Multi-Range Viscometer (HVM 472) determines kinematic viscosity of transparent and opaque liquids. The easy to operate HVM 472 includes 2 multi-range capillaries with 100 fold measuring range, requires only 18 ml, and delivers precise results. A revolutionary auto sampler offers truly continuous operation, spent sample vials automatically discharge, allowing new samples to be added at any time, even mid-test! For rapid analysis within viscosity range of 0.5 to 600mm<sup>2</sup>/s, the HVM 472 offers the smart alternative to run samples using 20-fold range Fast Run ("FR") capillaries.



1. Insert sample beaker into feeder



2. Enter sample number in software and indicate it either priority sample or added as next in line at the end of the sample order list



3. After the analysis is run, the used sample is collected in the discharger tray.

## ADVANCED SYSTEM AUTOMATION AND DESIGN FOR HIGH LEVEL OF STABILITY, SAFETY AND EASE OF USE



### Smart bath design

- Capillary tubes are visible from 360° direction
- Effective circulation system ensures bathes temperature uniformity
- Double cover glass wall to avoid direct contact with hot surface

### Reduced VOC emissions

Allows connection to ventilation system

### High quality and robust configuration

- Automated cleaning station, using 2 different solvents (up to 4 as option)
- Seal & valve system made of robust and corrosion resistant material
- No direct contact from operators

### Maximized sample throughput



- Two integrated sample changers for 7-8 hours unattended operation
- Capability to run 2x26 samples at two different temperatures
- Compatible with very viscous products, (option of individual sample preheating up to 120°C)

## USER-FRIENDLY SYSTEM CONTROL AND ANALYSIS SOFTWARE

The HVM 472 software includes a range of features for user-friendly control and optimized system operation:


### DIRECT ACCESS TO CRITICAL INFORMATION

- **Continuous monitoring of test progress for both baths:**  
Bath T°C, sample ID, measuring range of installed capillary, unit status and order no. in the sampler changer tray
- **Comprehensive results display:**  
Upto 400 results (local memory), sample ID, flow times (+ deviation to previous flow time) Status also available through PC software and print output




### RANGE OF ANALYSIS OPTIONS

- Common result database for several instruments
- Individual measuring program for each sample
- Automatic gravity and energy correction
- Automatic viscosity index calculation
- SUS-, dynamic viscosity- and M- value calculations
- Statistical flow times analysis (outlier detection)
- Repeatability and reproducibility calculation



### TOTAL QUALITY ASSURANCE

- **Factory calibration at both 40°C (104°F) and 100°C (212°F):**
  - Ready for immediate determination of VI
  - Up to 10 temperature points available per bath
- **Easy Calibration Procedure within 3 steps:**
  - Measure bath real temperature with a Certified Reference Thermometer
  - Enter the temperature reading into the instrument calibration table
  - The system automatically calculates the correction offset history information



### MULTIPLE UNITS NETWORK OPERATION

Users can choose to have the HVM 472 operate as a stand-alone unit or benefit from using it in a PC-controlled network with PAC IRIS Software. This advanced lab instrument data integration software is designed specifically for PAC instruments to gather and analyze test data and communicate results so customers can make informed decisions.

PAC IRIS offers:

- Improved laboratory efficiency
- Simplified knowledge sharing and decision making
- Designed to promote Good Laboratory Practices

