

HRB 754



The HRB 754 Ring & Ball Tester automatically determines Softening Point of bitumen, tar, pitch, tall oil rosins, and polymeric resins via standard ring and ball test methods. Tests start in four simple steps: insert the sample in the instrument, input the sample ID, select a pre-programmed test method, and press Start.


In addition to performing standard softening point tests, this versatile analyzer is easily programmed with your own customized test protocols. Test selection and other operational commands are entered via the instrument's easy-to-use touch screen display. The system even includes on-line help to guide you through operational procedures.



A. The HRB 754's "touch screen" display lets you quickly initiate standard softening point tests, change test parameters, run system diagnostics, and recall test results.



B. The HRB 754 displays measurement results on a bright, easy-to-read graphics display.



C. Up to 300 individual measurements can be stored in the HRB 754 for later viewing and analysis. Built-in statistical functions permit repeatability and standard deviation calculations.

ADVANTAGES

- Pre-programmed test procedures
- Stores up to 20 permanent and user-defined test programs
- Easy-to-use touch screen testing, programming, diagnostics, calibration
- Integral results database stores up to 300 measurements; incorporates statistical calculation and graphing capacity
- Built-in, user programmable air cooling system
- Stand-alone or networked operation

APPLICATION RANGE

- Softening Point
 - Bitumen
 - Tar
 - Pitch
 - Tall oil rosins
 - Polymeric resins
 - Waxes
 - Adhesives

STANDARD METHODS

- In accordance with:
- ASTM D36
 - ASTM E28
 - IP 58
 - ISO 4625
 - DIN 52011
 - NFT 66008
 - EN 1427



solidpartners proven solutions

U.S.A.

PAC, LP | 8824 Fallbrook Drive | Houston, Texas 77064
T: +1 800.444.TEST | O: +1 281.940.1803 | F: +1 281.580.0719
sales.usa@pacpl.com | service.usa@pacpl.com

FRANCE

BP 70285 | Verson | 14653 CARPIQUET Cedex
T: +33 231 264 300 | F: +33 321 266 293
sales.france@pacpl.com | service.france@pacpl.com

GERMANY

Badstrasse 3-5 | P.O.Box 1241 | D-97912 Lauda-Königshofen,
T: +49 9343 6400 | F: +49 9343 640 101
sales.germany@pacpl.com | service.germany@pacpl.com

SINGAPORE

61 Science Park Road | #03-09/10 The Galen
Singapore Science Park III | Singapore 117525
T: +65 6412 0890 | F: +65 6412 0899
sales.singapore@pacpl.com | service.singapore@pacpl.com

NETHERLANDS

P.O.Box 10.054 | 3004 AB Rotterdam
Innsbruckweg 35 | 3047 AG Rotterdam
T: +31 10 462 4811 | F: +31 10 462 6330
sales.netherlands@pacpl.com | service.netherlands@pacpl.com

RUSSIA

Shabolovka Street | 34, Bldg. 2 | 115419 Moscow
T: +7 495 617 10 86 | F: +7 495 913 97 65
sales.russia@pacpl.com | service.russia@pacpl.com

CHINA

Room 1003, Sunjoy Mansion | No. 6 RiTan Rd.
Chao Yang District | Beijing 100020
T: +86 10 650 72236 | F: +86 10 650 72454
sales.china@pacpl.com | service.china@pacpl.com

INDIA

1508 | Dev Corpora | Pokhran Road No.1
Eastern Express Highway | Thane (W) - 400 601
T: +91-22-6700 4848 | F: +91-22-4228 4950
sales.india@pacpl.com | service.india@pacpl.com

MIDDLE EAST

A1 Quds Street, A1 Tawar road | LIU#H13 Dubai Airport Freezone
Near Dubai Airport (terminal 2) | P.O.Box #54781 | Dubai, UAE
T: +971 04 2947 995 | F: +971 04 2395 465
sales.middleeast@pacpl.com | service.middleeast@pacpl.com

SOUTH KOREA

#621 World Vision Building | 24-2, Youido-dong
Seoul 150-010
T: +82 2785 3900 | F: +82 2785 3977
sales.southkorea@pacpl.com | service.southkorea@pacpl.com

THAILAND

26th Floor, M. Thai Tower | All Seasons Place
87 Wireless Road | Lumpini, Phatumwan | Bangkok 10330
T: +66 2627 9410 | F: +662627 9401
sales.thailand@pacpl.com | service.thailand@pacpl.com


PAC Authorized Representatives are also located in most countries worldwide. For more information visit www.pacpl.com

HERZOG BY PAC

Herzog, originally established in 1937, is a long-established comprehensive line of laboratory instruments for testing distillation, flash point, vapor pressure, bitumen testing, cold flow properties, viscosity and other physical properties of materials.

HRB 754 RING & BALL TESTER ABSOLUTE PRECISION

The HRB 754 incorporates laser light and phototransistor detection for ultra precise recognition of softening point. "Smart" software distinguishes between air bubbles and the falling balls. Plus, a multi-point calibration table ensures precision across a wide bath temperature testing range.



SPECIFICATIONS

Ordering Information	
	HRB 754 Ring & Ball Tester automatically determines softening point of samples up to 200°C or, with blower module, to 250°C. Easy touch-screen operation and a built-in, user programmable cooling system. - 07541-000-01 20° to 200°C (68° to 392°F) - 07541-000-02* 20° to 250°C (68° to 482°F) * includes blower module for increased upper temperature range
Test Program	
	Up to 20 permanent (ASTM D36, ASTM E28, IP 58, ISO 4625, DIN 52011, EN 1427, and NFT 66008) and user-defined test protocols
Operation	
Temperature Display	°C or °F
Heating Media	Water, silicone oil, glycerin, or glycol
Stirring	Magnetic stirring; programmable 0 to 250 rpm
Detection System	Laser light barrier
Temperature Measurement	PT100 probe; glass (standard) or stainless steel; delivered with calibration certificate
Documentation & Data	
	Locally stores up to 300 test results Parallel port for optional printer RS 232 serial port
Accessories	
Testing Accessories	253-124: Ball coupling cage for non-bituminous samples 413-037: Grip tongs for handling beaker after test 253-133: Pouring plate (EN 1427, ASTM D 36)
Printing Accessories	101-175: Needle printer (230V) 101-176: Needle printer (115V) 626-053: Printer cable
Diagnostics & calibration	
	Automatic calibration with programmable frequency, 21-point probe offset correction table Automatic diagnostic routines on analyzer functions, Upload/download service features via PC; calibration parameters and unit program backup/restore feature
Utility Requirements	
Electrical Requirements	Switch selectable; 115/230 VAC, 50/60 Hz, 1000 watts
Dimensions	250mm (W) x 500mm (D) x 512mm (H) 9.8" x 19.7" x 20.2"
Weight	24 kg / 53 lbs

Copyright 2012/1 PAC L.P. All rights reserved 820-177

www.pacpl.com



USA • FRANCE • GERMANY • NETHERLANDS • UAE • RUSSIA • CHINA • SINGAPORE • SOUTH KOREA • THAILAND • INDIA